

Performance assessment of carbon capture applied to combined cycle gas turbine under part-load operation

5th Consortium Meeting - May 23th, 2022

Antoine Verhaeghe

Under the supervision of Ward De Paepe and Laurent Bricteux

antoine.verhaeghe@umons.ac.be



Objective

Assessment of the techno-economical feasibility of applying **Post Combustion Carbon Capture (PCCC)** to a **micro Gas Turbine (mGT)** and a typical Belgian **Combined Cycle Gas Turbine (CCGT)**

Workplan

1. Micro Gas Turbines
2. Combined Cycles Gas Turbines

Workplan

1. Micro Gas Turbines
2. Combined Cycles Gas Turbines


Carbon capture process improvement for mGT application

Carbon capture process improvement

Conventional MEA [process optimisation](#)

Implementation of another solvent [MDEA/PZ](#)

Implementation of more [advanced configurations](#)



Workplan

1. Micro Gas Turbines
2. Combined Cycles Gas Turbines

Problematic

CCGTs are increasingly used as **peak units** to back-up the **intermittent** renewable production

CCGTs operate mostly at **partial load**

The carbon capture design is typically based on the CCGT **full load** operation

The carbon capture **performance** is usually assessed at full load

The real impact of CCGT off-design operations on carbon capture performance and plant profitability is unknown

Objectives

Assessment of the **performance** of carbon capture plant applied to a typical CCGT power plant under various operation conditions

Assessment of the impact of **realistic** CCGT operating conditions over a year on the **profitability** of the plant

Approach

The carbon capture plant is considered as an **end-of-pipe unit** without modifying the CCGT to **retrofit** existing power plants

Steady-state thermodynamic cycle modelling

Methodology

CCGT flue gas properties prediction with Thermoflow

Carbon capture modelling approach


- Pilot-scale carbon capture modelling and validation
- Scale-up of the carbon capture plant
- Optimisation of the carbon capture process

CCGT flue gas properties were obtained using Thermoflow


Generic H-class GT and 3 pressure level steam with reheat

Thermoflex simulation

CCGT load: from 100% to 30%



Thermodynamic cycle modelling of the CC plant with Aspen Plus



The numerical model is validated

Pilot-scale Advanced Capture Technology (**PACT**) at UK Carbon Capture and Storage Research Centre (**UKCCSRC**)

	Absorber	Stripper
Diameter (m)	0.303	0.303
Packed height (m)	6	6
Packed type	IMPT#40	IMPT#40

L/G=1.86 kg/kg		Experimental data	Numerical model	Relative difference [%]
Rich CO ₂ loading	[molCO ₂ /molMEA]	0.409±0.001	0.411	0.56
CO ₂ captured	[kg/h]	16.47±0.4	16.48	0.07
CO ₂ capture efficiency	[%]	90.35±3	90.38	0.04
Specific reboiler duty	[MJ/kg _{CO₂}]	5.92±0.8	5.81	1.77

L/G=3.77 kg/kg		Experimental data	Numerical model	Relative difference [%]
Rich CO ₂ loading	[molCO ₂ /molMEA]	0.247±0.001	0.246	0.4
CO ₂ captured	[kg/h]	16.3±0.59	16.09	1.31
CO ₂ capture efficiency	[%]	94.93±4.2	93.73	1.27
Specific reboiler duty	[MJ/kg _{CO₂}]	13.27±2.21	15.67	18.09



Scale-up of the carbon capture plant for CCGT application

	Absorber	Stripper
Diameter [m]	18	8.5
Height [m]	30	30

Columns diameter?

Avoid flooding in the absorber and the stripper

Columns height?




The CC process is optimized to minimize its energy consumption for each CCGT load


The **L/G** ratio has a high influence on the **SRD** for each CCGT load

If the CCGT load **decreases**:

- Optimal L/G **decreases**
- SRD **increases**




The heating duty increases, while the cooling duty decreases when the CCGT load is reduced



$$SCD = \frac{Q_1 + Q_2 + Q_3}{\dot{m}_{CO_2}}$$

$$SHD = \frac{Q_4}{\dot{m}_{CO_2}}$$



Different CCGT annual operations scenarios are analysed

	Scenario 1	Scenario 2	Scenario 3	Scenario 4
Annual load factor	1	0.5	0.5	0.75
Net electrical production [GWhe/y]	2109	2098	1050	2105

CCGT load	30%	40%	50%	60%	70%	80%	90%	100%
Scenario 1 [h]	-	-	-	-	-	-	-	4000
Scenario 2 [h]	3000	-	3000	2000	-	-	-	-
Scenario 3 [h]	1000	1000	1000	1000	-	-	-	-
Scenario 4 [h]	-	600	-	1500	-	2200	-	1000

CCGT part-load operations impact negatively CC performance

	Scenario 1	Scenario 2	Scenario 3	Scenario 4
Annual load factor	1	0.5	0.5	0.75
Net electrical production [Gwhe/y]	2109	2098	1050	2105
Energy input without CC [kWh/kWhe]	1.64	1.86 +12%	1.86 +12%	1.71 +4%
Energy input with CC [kWh/kWhe]	2.12	2.44 +15%	2.44 +15%	2.22 +5%
Increase in energy input due to the CC [kWh/kWhe]	0.48	0.58 +21%	0.58 +21%	0.51 +6%
CO ₂ emissions without CC [g/kWhe]	326	370	370	341
CO ₂ emissions with CC [g/kWhe]	35	40	40	37

Conclusions

Most of the studies evaluate carbon capture performance at **full-load** CCGT operation

Carbon capture performance **negatively impacted** by part-load CCGT operation

Useful insight for a thorough **economic** analysis

Decision-making about carbon capture should be based on analysis considering realistic CCGT operating conditions

Next steps

Micro Gas Turbine (mGT)

- Other **advanced CC configurations** (in progress)
- **Energy integration** between the mGT and the CC

Combined Cycle Gas Turbine (CCGT)

- Impact of **Exhaust Gas Recirculation** (EGR)
- **Energy integration** between the CCGT and the CC

Performance assessment of carbon capture applied to combined cycle gas turbine under part-load operation

5th Consortium Meeting - May 23th, 2022

Antoine Verhaeghe

Under the supervision of Ward De Paepe and Laurent Bricteux

antoine.verhaeghe@umons.ac.be

